## FBO-14-DPL

Fuel Filter/Water Separator
Provides CLEANDiesel® For Connaughton
Sand & Gravel Itd

## **Market Application Publication**



## **Application**

Fuel dispensing bund tank, Athlone Co. Westmeath

### The Problem

Connaughton Sand & Gravel Ltd were suffering from algae and water contamination in their diesel storage tank causing injector issues, excessive exhaust smoke and coolant pump corrosion from their fleet of Volvo CE wheel loader, excavators and dump trucks.

#### Solution

Fuel Dispensing FF/WS, Part Number FB0-14-DPL.

- Heavy-duty assembly
- Water separator element
- · Delta P gauge
- · Sight glass
- · Drain valve

## **Contact Information**

Fortismet Itd Moydrum Road Athlone Co. Westmeath Ireland

www.fortismet.ie info@fortismet.ie phone +353(0)87 331 4443





## Why Racor was chosen as the solution

The FBO-14 filter assemblies are designed to meet the toughest fuel refueling conditions and offer easy cartridge changeouts.

FBO Series offers a compact way to deliver clean diesel.

These versatile housings have three filter options to meet various requirements: a fuel filter/water separator, a silicone treated filter, and a water absorber. For fuel dispensing applications the fuel filter/water separator element is recommended.



**ENGINEERING YOUR SUCCESS.** 



#### **How the Solution Works**

Racor's great reputation and wide selection of products made us the perfect solution. The size of units, water separator elements, a wide variety of micron ratings, ability to drain water, differential pressure gauge, longer life than spin on and ease of service made the FBO-14-DPL the perfect solution for the application.



# Filter Cartridge Chart

FB0	Micron Rating	Water Separator	Silicone Treated Filter	Water Absorber
FBO-14 (6 X 14 Element)	1	FB0 60336	FB0 60339	FB0 60342
	5	FB0 60337	FB0 60340	FB0 60343
	10	FB0 60356	FB0 60357	FB0 60358
	25	FB0 60338	FB0 60341	FB0 60344



# **Technical Information**

Specifications	Ma	Maximum Flow Rates			Change
FBO-14	Diesel	Gasoline	Kerosene	Delta P	Delta P
Silicone Treated Filter	30 GPM (113 LPM)	75 GPM (284 LPM)	50 GPM (189 LPM)	2.5 PSID	15 PSID
Water Separator	25 GPM (95 LPM)	45 GPM (170 LPM)	30 GPM (113 LPM)	2.5 PSID	15 PSID
Water Absorber	25 GPM (95 LPM)	70 GPM (265 LPM)	55 GPM (208 LPM)	2.5 PSID	30 PSID



© 2014 Parker Hannifin Corporation. Product names are trademarks or registered trademarks of their respective companies.





Moydrum Road Athlone Co. Westmeath Rep of Ireland +353873314443 +353906485188 info@fortismet.com www.fortismet.ie

Fortismet Ltd